




## *4 Channel Portable Online Partial Discharge Analyzer*



### *Key Features* \_\_\_\_\_

- PD Acquisition according to IEC60270
- High Resolution PRPD Pattern
- Noise Elimination through Gating Channel and variable Frequency Range
- Local True Color Touch LCD
- 4 Channel Simultan Data Acquisition
- User friendly Software

TMS-6141

### *Applications* \_\_\_\_\_

- Turbo Generators
- Hydro Generators
- Large Industrial Motors
- Windmills

### *General Description* \_\_\_\_\_

The **TMS-6141** is a four channel portable partial discharge analyzer with a true color LCD display showing all the necessary information for the analysis of high voltage rotating machines. The noise gating channel and variable Filters allows to separate noise from the pd signals. True simultaneous data acquisition over all channels allows a time relation analysis between each channel. This additional Time Relation Pattern analysis (TR-Pattern) allows to easy separate discharges between ground and discharges between phases. The **TMS-6141** shows in realtime actual pd activity in oscilloscope mode as well as color phase resolved partial discharge patterns for every individual channel (phase). The touch functionality of the color LCD display allows to operate, parametrise and visualise the partial discharge signals without the use of any computer. Optionally a computer can be connected to show and store real time partial discharge results. This make the **TMS-6141** the ideal portable online partial discharge analyzer for rotating machines.

### *Ordering Information* \_\_\_\_\_

Order Code: 17.6141.000.000.000.000

## 4 Channel Portable Online Partial Discharge Analyzer



### Technical Data

TMS-6141

#### Data Acquisition of Partial Discharge Channels

PD Input Channels (simultaneous):	4	Signal Gain (HW):	40dB
Frequency Range		Pulse deadtime:	20us
Selectable LP Filter:	40KHz to 5MHz	A/D Resolution:	16bit
Selectable HP Filter:	800kHz to 300MHz	Acquisition Time Intervall:	1 to 600 sec/ch
Signal Gain (HW):	40dB	Gating Channel:	1
Gating Channel:	1	Frequency Range	
Frequency Range		Selectable LP Filter:	40KHz to 5MHz
Selectable LP Filter:	40KHz to 5MHz	Selectable HP Filter:	800kHz to 300MHz
Selectable HP Filter:	800kHz to 300MHz	Sensor Compatibility:	
		Coupling Capacitors:	80pF - 10nF <sup>1)</sup>
		RF CT's:	yes <sup>1)</sup>

<sup>1)</sup> Effective Frequency Range of PD Channel depends on selected sensor Type

#### Voltage References

Reference from Coupler	10mV to 30Vrms	From Power Supply:	max 260VAC
Frequency Range:	0.1 to 200Hz	External Voltage Reference:	max 260VAC

#### Interfaces

Ethernet: 100Mbit

#### Display

Dimension:	5.7"	Color Depth:	24bit
Resolution:	640 x 480pxl	Touch:	Resistive

#### Local Results

Phase Resolved Partial Discharge Pattern:	Time Relation Pattern
Resolution & Color: 256x256 - 16bit Color	Oscilloscope Mode

#### Mechanical Dimensions

Dimensions (L x W x D)	220 x 160 x 80mm	Protection Class:	IP55
Weight:	3.5kg		

Sparks Instruments reserves the right, without further notice, to change the product specifications and/or the information on this document to improve reliability, functions and design of this product. © 2011, Sparks Instruments, All rights reserved.

#### Contact

**Sparks Instruments SA**  
Bodematta 12, 1714 Heitenried  
Switzerland

Email: sales@sparksinstruments.com  
Web: www.sparksinstruments.com

Worldwide Exclusive Sales Representative  
& Tech Support

**MC** MC-monitoring SA  
Measuring - Consulting - Monitoring  
Route des Daillettes 6  
1709 Fribourg, Switzerland  
Phone: +41 26 401 84 56  
Email: sales@mc-monitoring.com